



Water Blasting Protection Boots

Up to 500 Bar



| Size | Part No |
|------|------------|
| 36 | 92.50.0036 |
| 37 | 92.50.0037 |
| 38 | 92.50.0038 |
| 39 | 92.50.0039 |
| 40 | 92.50.0040 |
| 41 | 92.50.0041 |
| 42 | 92.50.0042 |
| 43 | 92.50.0043 |
| 44 | 92.50.0044 |
| 45 | 92.50.0045 |
| 46 | 92.50.0046 |
| 47 | 92.50.0047 |
| 48 | 92.50.0048 |

| Protection Level | Pressure (Bar) | Flow Rate (l/min) | Nozzle Type | Distance (mm) | Speed (m/s) | Result |
|------------------|----------------|-------------------|--------------------|---------------|-------------|----------------|
| 5/5/2 | 500 | 16.9 | Rotor - Rotary jet | 75 | 0.5 | No penetration |
| 5/5/2 | 500 | 16.9 | Flat - Single fan | 75 | 0.5 | No penetration |
| 5/5/2 | 200 | 10.7 | Single - Single | 75 | 0.5 | No penetration |

The protective coating is at the front of the foot area and has a different color and texture.
CE-marking: Approved according to the directive EN 345S5.

